

EKHO

INFRASTRUCTURE
SOLUTIONS



ALUMINUM NOISE BARRIER SYSTEM

An engineered noise barrier system

A new horizon of infrastructure possibilities


ekhois.com

A Customer Focused, Noise Barrier Solutions Provider

EKHO is a reliable source for convenient transportation and building noise barrier solutions. Our light-weight panels are adept at absorbing or reflecting noise, cost-effective, and can accommodate even the most demanding construction schedule.

ALUMINUM NOISE & SAFETY BARRIERS

From roadside safety to perimeter security, our customized aluminum wall system is a long-term solution for your project.



Easy Installation completed with limited crew & equipment.

Reduce unwanted noise caused by HVAC equipment, loading docks, traffic and more.

Custom colors to meet project requirements.

APPLICATIONS



Industrial,
Commercial,
Institutional
Properties



Roads,
Highways
& Bridges



Rail &
Transit



Building
Rooftop
Screens



Perimeter
Walls &
Enclosures



AN ENGINEERED SYSTEM AT THE SPEED YOU NEED

Our aluminum noise walls can be engineered by our in-house team to meet specific wind load requirements, supplying a turnkey wall system that is a safer, easily installed solution alongside roadways and on building properties.

LIGHT-WEIGHT & CUSTOMIZABLE

Prefabricated for a wide range of noise mitigation, the light-weight panels are easy to work with offering drop-in-place installation and tongue and groove assembly.



FEATURES & BENEFITS



Light-weight panels

- Reduces 'dead' loading for structure mounted applications.



Acoustic properties

- Single-sided or dual-sided absorptive panels.
- Reflective panels.



Safety & Engineering

- Engineered to meet design criteria.



Easy-installation

- Easy panel handling.
- Tongue & groove jointed panels for secure connection.
- Reduces need for heavy equipment at installation.



Durability


- Low Maintenance.



Colored finishes

- Powder or coil coated colors.


ABSORPTIVE PERFORATED PANEL



EKHO AL1S NOISE BARRIER PANEL

- Manufactured with perforations and acoustic mineral wool enclosed.
- Proven and tested properties to reduce noise.


DUAL ABSORPTIVE PERFORATED PANEL



EKHO AL2S NOISE BARRIER PANEL

- Perforated on both sides of panel with a double layer of acoustic mineral wool enclosed.
- Ideal for projects with multiple noise sources.

SMOOTH REFLECTIVE CUSTOM COLOR PANEL



EKHO AL3S NOISE BARRIER PANEL

- Reflects noise source back.
- Reflective panels can be used in combination with absorptive panels in walls designed to mitigate noise in specific areas.

Proactive Noise Reduction & Property Protection

Shelter noise-emitting mechanical equipment or busy loading docks and achieve an enhanced level of privacy and security for the premises.

DESIGN DETAILS

Panels:

- 5 inches thick.
- Maximum 5.2lbs / sq ft density.
- Panel height 1.64 ft.

Post:


- Design for W6 posts or larger.
- Structure-mounted hot dipped galvanized steel posts connected with steel cable option for improved safety.
- Retention cables designed for structure mounted walls.
- Panel lengths available up to a maximum of 20 ft long.

Wall Height:

- Wall heights are achieved by stacking panels to the project requirements.

Panel Type	Dimensions	System Weight
EKHO AL1S	Aluminum individual panels available: 19.7" H x 5" W Panel lengths up to 20'	13.5 kg/ m ² or 2.8 lbs/ ft ²
EKHO AL2S		25.2 kg/ m ² or 5.2 lbs/ ft ²
EKHO AL3S		9 kg/ m ² or 1.8 lbs/ft ²

Test No.	Results
ASTM E84	FLAME SPREAD = 0 SMOKE DEVELOPED INDEX ≤15
ASTM C423	0.90 NRC RATED (AL2S) 0.95 NRC RATED (AL1S)
ASTM E90	33 STC RATED (AL2S) 26 STC RATED (AL1S) & (AL3S)



EKHO MASH TL-4 Noise Barrier System

CRASH-TESTED PEACE-OF-MIND


The EKHO MASH TL-4 Noise Barrier System has been tested to MASH (Manual for Assessing Safety Hardware) TL-4 crash-testing criteria. As dictated by AASHTO (the American Association of State Highway and Transportation Officials), the impact speed and angle of the crash represents the worst practical condition so that transportation professionals can design with safety assurance.

AASHTO MASH TL-4 Criteria


VEHICLE	10,206 kg Box Truck
SPEED	58 mph
VEHICLE	15°
TEST NO.	4-12



Despite the severity of the impact, the MASH TL-4 Aluminum Noise Barrier provided excellent vehicle stability. The wall panels remained intact, and minimal damage was recorded. Tested at heights of 17' with a maximum post width of 10'.



MASH 4-12 Sequentials





ALUMINUM NOISE BARRIER SYSTEM

EKHO

INFRASTRUCTURE
SOLUTIONS

Canada: 45 Frid Sreet, Suite 1, Hamilton, ON L8P 4M3

U.S.A.: 10 Campus Boulevard, Suite 103, Newtown Square, Pennsylvania, 19073

email@ekhois.com

ekhois.com

